

DATA SHEET

TL810K01 Compact Product Suite hardware selector



Select I/O is an Ethernet networked, single channel granular I/O system for the ABB Ability[™] System 800xA automation platform. Select I/O helps decouple project tasks, minimizes the impact of late changes and supports standardization of I/O cabinetry ensuring automation projects are delivered on-time and under budget. A Signal Conditioning Module (SCM) performs the necessary signal conditioning and powering of the connected field device for one I/O channel.

Empty slot protector for a Fieldbus Communication Interface slot on the Ethernet FCI Module Termination Unit. 10 pieces per package.

Features and benefits

• Empty slot protector for a Fieldbus Communication Interface slot on the Ethernet FCI Module Termination Unit

General info	
Article number	3BSE088170R1
Туре	Empty slot protector for FCI
Hot swap	Yes
Mechanics	Select I/O

Detailed data		
Installation in Hazardous Area/Locations	ATEX – II 3G Ex nA/eC IIC T4 Gc	
	Class I, Zone 2, IIC T4	
	Class I, Div 2, Groups A, B, C, D T4	
	Non-arcing field wiring acc. to Division model	

Environment and certification		
Temperature, Operating	-40°C (-40°F) to +70°C (158°F)	
Temperature, Storage	-40°C (-40°F) to +85°C (185°F)	
Pollution degree	Pollution Degree 2 acc. to IEC 60664-1	
Relative humidity	5 to 95 % no condensation	
Altitude	-1000 to 3000 m, (-100 2000 m for Zone 2/Class I Div 2)	
Mechanical operating conditions	IEC 61131-2	
EMC	IEC/EN 61000-6-4, IEC/EN 61000-6-2	
Overvoltage categories	Category II, IEC 60664-1	
Protection class	IP20 according to IEC 60529	
CE-marking	Yes	
Electrical Safety	IEC/EN 61010-1, IEC 61010-2-201, UL 61010-2-201, CSA C22.2 No. 61010-2-201	
Hazardous Area	EN 60079-0, EN60079-7, EN60079-15, UL 12.12.01 / CSA C22.2 No. 213-17	
Marine certification	ABS	
Corrosive atmosphere	G3 (ISA-S71.04)	
RoHS compliance	DIRECTIVE/2011/65/EU (EN 50581:2012)	
WEEE compliance	DIRECTIVE/2012/19/EU	

Dimensions	
Width	134.5 mm (5.30 in.)
Depth	38.5 mm (1.52 in.)
Height	29 mm (1.14 in.)
Weight (including base)	35.5 g (0.07 lbs)



solutions.abb/compactproductsuite solutions.abb/controlsystems

_

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document. We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2025 ABB All rights reserved