


DATA SHEET

## Mains Breaker kit, DIN Rail

## Compact Product Suite hardware selector





## Features and benefits

- 3 fused (6.3 A) double output terminals
- Kit fit for most global connection needs
- DIN rail mount

Detailed data

Maximum ambient temperature

General info		
Article number	3BSE022262R1	
Туре	Mains Breaker kit	
Rated output current	3 fused (6.3 A) double output terminals	
Mains/input voltage, nominal	115/230 V	

55 °C

Environment and certification		
CE mark	Yes	
Marine certification	ABS, BV, DNV-GL, LR	
Corrosive atmosphere ISA-S71.04	G2	
Climatic operating conditions	5 to 95 % no condensation	
Pollution degree	Degree 2, IEC 60664-1	
Mechanical operating conditions	IEC 61131-2	
EMC	EN 61000-6-4 and EN 61000-6-2	
Overvoltage Categories	IEC/EN 60664-1	
Equipment class	Class 1 according to EN 50718; 3.56	
RoHS compliance	DIRECTIVE/2011/65/EU (EN 50581:2012)	
WEEE compliance	DIRECTIVE/2012/19/EU	

Dimensions	
Width	102.5 mm (4.04")
Weight (lbs.)	0.5 kg (1.1 lbs.)



solutions.abb/compactproductsuite solutions.abb/controlsystems

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2025 ABB All rights reserved