

# TU890

## Compact Product Suite hardware selector



The TU891 is a compact MTU for the S800 I/O. The MTU is a passive unit used for connection of the field wiring and power supply to the I/O modules. It also contains a part of the ModuleBus. The TU891 MTU has gray terminals for field signals and process voltage connections. The maximum rated voltage is 50 V and maximum rated current is 2 A per channel, but these are primarily constrained to specific values by the design of the I/O modules for their certified application.

The MTU distributes the ModuleBus to the I/O module and to the next MTU. It also generates the correct address to the I/O module by shifting the outgoing position signals to the next MTU.

### Features and benefits

- Intrinsic safety applications - use with AI890, AI893, AI895, AO890, AO895, DI890 and DO890
- Compact installations of I/O modules
- Field signals and process power connections
- Connections to ModuleBus and I/O modules
- Mechanical keying prevents insertion of the wrong module
- Latching device to DIN rail
- DIN rail mounting

| General info         |   |
|----------------------|---|
| Article number       | 3BSC690075R1                                    |
| Type                 | Compact   |
| Connection           | Terminal block                                  |
| Channels             | 8   |
| Voltage              | 24 V  |
| Mounting             | Horizontal                                      |
| Mounting detail      | 55 ° (131 °F)                                   |
| Use with I/O         | AI890, AI893, AI895, AO890, AO895, DI890, DO890 |
| Process connections  | 27 blue terminals                               |
| Single/redundant I/O | Single  |

| Detailed data                   |  |
|---------------------------------|--|
| Maximum current per I/O channel | 2 A  |
| Acceptable wire sizes           | Process Connector:<br>Solid 0.2 - 4 mm <sup>2</sup><br>Stranded 0.2 - 2.5 mm <sup>2</sup> , 24 - 12 AWG<br>Recommended torque 0.5 - 0.6 Nm<br><br>Power supply connector:<br>0.25 - 2.5 mm <sup>2</sup> , 24 - 14 AWG<br>Recommended torque 0.5 - 0.6 Nm |
| Dielectric test voltage         | 500 V a.c.   |

| Environment and certification   |  |
|---------------------------------|--|
| CE mark                         | Yes  |
| Electrical safety               | EN 61010-1, EN 61010-2-201   |
| Hazardous Location              | ATEX/IECEx Zone 2 with interface to Zone 0, cFMus C1, Div 2/Zone 2 with interface to C1, C2, C3 Div 1/Zone 0 |
| Marine certification            | ABS, BV, DNV-GL, LR  |
| Temperature, Operating          | 0 to +55 °C (+32 to +131 °F) (Storage -40 to +70 °C) (-40 to +158 °F), RH=5 to 95 %, non-condensing          |
| Pollution degree                | Degree 2, IEC 60664-1  |
| Corrosion protection            | ISA-S71.04: G3   |
| Max ambient temperature         | 55 °C (131 °F), for vertical mounting 40 °C (104 °F)   |
| Protection class                | IP20 according to IEC 60529  |
| Mechanical operating conditions | IEC/EN 61131-2   |
| EMC                             | EN 61000-6-4, EN 61000-6-2   |
| Overvoltage categories          | IEC/EN 60664-1, EN 50178   |
| Equipment class                 | Class I according to IEC 61140; (earth protected)  |
| RoHS compliance                 | EN 50581:2012  |
| WEEE compliance                 | DIRECTIVE/2012/19/EU   |

| Dimensions |  |
|------------|--|
| Width      | 64 mm (1.77 in.) including connector, 58.5 mm (2.3 in.) edge to edge installed |
| Depth      | 58 mm (2.28 in.), 106 mm (4.2 in.) including terminals                         |
| Height     | 194 mm (7.6 in.) including latch   |
| Weight     | 0.17 kg (0.37 lbs.)  |

---

**[solutions.abb/compactproductsuite](https://solutions.abb/compactproductsuite)  
[solutions.abb/controlsystems](https://solutions.abb/controlsystems)**

---

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2025 ABB All rights reserved