

DATA SHEET

AIS885

Compact Product Suite hardware selector



Select I/O is an Ethernet networked, single-channel granular I/O system for the ABB AbilityTM System 800xA automation platform. Select I/O helps decouple project tasks, minimizes the impact of late changes, and supports standardization of I/O cabinetry ensuring automation projects are delivered on time and under budget. A Signal Conditioning Module (SCM) performs the necessary signal conditioning and powering of the connected field device for one I/O channel.

The AIS885 is an Analog Input Signal Conditioning Module (16-bit) for use in High Integrity applications (certified for SIL3) supporting 2/3/4-wire devices (1.2 amp) and HART communications.

Features and benefits

- Analog input for 2-wire, 3-wire or 4-wire field devices, powered by AIS885
- Signal range: 4...20 mA
- Can be used in hazardous areas
- Certified for Functional safety
- Field power sourced from the power injection
- Short circuit proof, configurable current limit 0.1 to 1.2 A
- Transmitter power current limited to 25 mA (for 2-wire field devices; input current limitation for SCM pin 2)
- 16 bit A/D converter resolution
- Galvanic isolation
- Protected against wrong wiring (±35 V) between all terminals
- Hardware filter, rise time 1 ms
- Software filter configurable through parameters
- Diagnostics:
 - Loop supervision (open circuit and short circuit)
 - Internal hardware supervision
 - Communication supervision
 - Device malfunction low, under range, over range and device malfunction high detection
 - Internal power supervision
 - Power injection supervision
- LED indicators:
 - Status (S)
 - Primary (P)
- Single loop granularity each SCM handles a single channel
- Supports hot swar
- Mechanical locking slider which turns off field device power and/or output before removal
- Field disconnect function which can galvanically separate the field loop wiring from the SCM during commissioning and maintenance
- All SCMs have electronic current limitation
- Mechanical keying to prevent insertion of wrong module type after commissioning
- 24V DC powered through Modulebus
- Configurable through parameters
- LED indicators on the SCM indicate the operational state of the module.

General info		
Article number	3BSE080108R1	
Туре	Analog Input Module, SIL3	
Number of channels	1	
Signal specification	420 mA 1.2 A field power	
HART	Yes	
Detailed HART information	HART v7, HART pass-through and HART variables to the application	
SOE	N/A	
Redundancy	Yes	
Hot swap	Yes	
High integrity	Yes	
Intrinsic safety	No	
Mechanics	Select I/O	

Detailed data		
Supported field devices	2-wire (loop powered transmitters), 3-wire (transmitters powered by SCM), 4-wire (transmitters powered by SCM)	
Isolation	Galvanic isolation to system. Routine tested at factory with 3060 V DC.	
Field power	Current limited (configurable)	
Accuracy	0.1 %	
Resolution	16 bit A/D converter	
Diagnostics	Loop supervision (open circuit and short circuit) Device malfunction low, under range, over range, and device malfunction high Internal hardware supervision Communication supervision Internal power supervision Power injection supervision	
Calibration	Factory calibration	
Power dissipation	0.65 W	
Installation in Hazardous Area/Locations	Yes/Yes (on IPA)	
IS barrier	No	
Field Input Robustness	±35 V between all terminals	
Input voltage range	19.230 V	
Input impedance	250 ohm	

Environment and certification		
Temperature, Operating	-40 °C (-40 °F) to +70 °C (158 °F)	
Temperature, Storage	-40 °C (-40 °F) to +85 °C (185 °F)	
Pollution degree	Pollution Degree 2 acc. to IEC 60664-1	
Relative humidity	5 to 95 %, non-condensation	
Altitude	-1000 to 5000 m (restrictions apply)	
Mechanical operating conditions	IEC 61131-2	
EMC	IEC/EN 61000-6-4, IEC/EN 61000-6-2	
Overvoltage categories	Category II acc. to IEC 60664-1	
Protection class	IP20 acc. to IEC 60529	
CE-marking	Yes	
UKCA	Yes	
Electrical Safety	IEC/EN 61010-1 UL 61010-1 CSA-C22.2 No. 61010-1-12 IEC/EN 61010-2-201 UL 61010-2-201 CSA C22.2 No. 61010-2-201	
Marine certification	DNV, ABS	
Corrosive atmosphere	G3	
RoHS compliance	EU RoHS, UAE RoHS, CN RoHS	
WEEE compliance	EU	
Hazardous Area ATEX	II 3G Ex ec IIC T4 Gc	
Hazardous Area IECEx	Available on IPA: II 3G Ex ec IIC T4 Gc	
Hazardous Location US/CAN	Available on IPA: cULus CL I, ZN 2, AEx ec IIC T4 Gc, Ex ec IIC T4 Gc X CL I, DIV 2, Groups A-D T4	
Hazardous Area CCC	Ex ec IIC T4 Gc	
Functional Safety	IEC 61508 Ed. 2, SIL 1-3 IEC 61511-1 IEC 62061 IEC 61131-2, IEC 61131-6 IEC 60204-1 NFPA 72, NFPA 79, NFPA 85, NFPA 86 EN ISO 14118 EN 50156-1 EN 298 EN 54-2, EN 54-2 A1 EN ISO 13850	

Dimensions		
Width	77.9 mm	
Depth	105 mm	
Height	9.8 mm	
Weight (including base)	73 g	



solutions.abb/compactproductsuite solutions.abb/controlsystems

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2025 ABB All rights reserved